

## SOP

## 750 Gallon Brine Maker

Follow the steps as listed for your 750 Gallon Brine Made Easy.

## Steps For Making Brine

- 1. Fill Gas and Check Oil in Honda Gas Powered Unit.
- 2. Close all Ball Valves, attach fill hose from Brine Maker to Application Devise or Storage Tank.
- 3. Fill Tank with 625 Gallons of clean water.
- 4. Open Circulation Valve.
- 5. Start Honda Motor
- 6. Begin to slowly add 28-50 lb. bags of Rock Salt.
- 7. After the 28th-50 lb. bags of Rock Salt is added, run for 20 min in circulation mode.
- 8. Remove test mixture in separate container.
- 9. Test Brine mixture with Salometer Meter to insure 23 to 24% solution.
- 10. Open value to empty Brine into Storage Tank or Application Devise.
- 11. Do not completely empty Brine Maker close the Valve to Storage Tank or Application devise while opening the circulation valve.
- 12. Begin again with step 3 as needed to fill Storage Tanks or Application Device.

## Brine Maker Cleanup and Storage Procedures.

- 1. Load 25 gallons of water.
- 2. Start Motor after checking Gas and Oil.
- 3. Open Circulation Valve.
- 4. Circulate for 5 minutes.
- 5. Close Circulation Valve
- 6. Attach fill hose from Brine Maker to Storage Tank, open Valve pump mixture into Storage Tank or Application Device
- 7. Repeat as needed to insure Pump and Hoses are free of debris.
- 8. Remove Filter and clean with water.
- 9. Remove Drain Plug from Pump housing.
- 10. Brine Maker is ready for storage.
- 11. Dispose of Rock Salt Bags and other trash in approved refuse area.
- 12. Clean up all Rock Salt Spills and Dispose of properly